



- Entry level IP phone
- Compatible with major platforms
- 2 SIP lines
- 8 programmable GSK
- PoE
- IPv6
- Supports audio codec G.722 and Opus



Part Code
V3000IP

ACE V3000IP Phone

Phone Features

- Call logs (In/out/missed. max support 600 records on the web)
- Web Dial, dial plan
- SIP hotspot
- 8 Programmable DSS keys
- Action URL/ Active URI
- Multicast
- Distinctive ring tone

Networking

- 10/100Mbps Ethernet
- IP Mode: IPv4/IPv6/IPv4&6
- IP Configuration: Static/ DHCP/ PPPoE
- Network Access Control: 802.1x
- VPN: L2TP/OpenVPN
- VLAN:802.1P/Q
- Qos
- LLDP
- VQM: Voice quality monitoring



HIGHLIGHTS & COMPATIBILITY

V6000IP

Contemporary Hotel Phone with USB charging port on base, compatible with major platforms: 3cx, Broadsoft, Elastix, Asterisk, Xorcom. etc



3000IP Phone Continued

Advanced Features

- Call out/ answer
- Mute/ unmute
- Call hold/resume
- Speed dial
- Redial
- Call forward (always/busy/ no answer)
- Call transfer (attended/unattended)
- Hot line
- Voice Message

Network

- 10/100 Mbps Ethernet
- IP Mode: IPv4/IPv6/IPv4&IPv6
- IP Configuration: Static/DHCP/PPoE
- Network access control: 802.1x
- VPN:L2TP/OpenVPN
- VLAN: 802.1P/Q
- QoS
- LLDP
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)

Protocols

- SIP v1 (RFC2543),v2 (RFC3261) over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN - 1 hands-free indicator
- MSG indicator with red LED
- Desktop or Wall Mountable



Audio

- Wideband ADC/DAC/16KHz sampling
- Codec: G.711A/U, G.729AB, G723.1, G726,iLBC
- Wideband Codec: G.722 Opus
- Full-duplex hands-free speakerphone with AEC
- Voice Activity Detection (VAD)/ Comfort Noise Generation (CNG)/ Background Noise Estimation (BNE)/ Noise Reduction (NR)
- Packet loss concealment
- Dynamic Adaptive jitter buffer
- DTMF:in-band, out-of-band-DTMF-relay (RFC2833)/SIP Info
- VQM voice quality monitoring

Specifications

- Power: 5V/0.6A or PoE
- Handset: RJ9
- Power consumption PoE:1.28W~2.12W,
- Power consumption (Adapter): 0.669W ~1.438W
- Working temperature: 0~45°C
- Working humidity 10~95%

Deployment & Management

- Auto-provisioning via FTP/TFTP/HTTP/HTTPS/CHCP OPT66/SIP PNP/TR-069
- Web management portal
- Web-based packet dump
- Configuration import/export
- Firmware upgrade
- Syslog



Part Code
V3000IP